


BLDC Motor | [DLA4885/DLB4885] Brushless DC Motor



특징 FEATURES

- ◆ **Application** : Refrigerator Evaporator or Condenser fan motor
- ◆ **Input Voltage** : DC 7 ~ 15V
- ◆ **Motor type** : 3 Phase
- ◆ **Drive type** : Sensor or Sensorless
- ◆ **Speed Control** : DC voltage or PWM
- ◆ **Output Rotation** : C.W or C.C.W
- ◆ **Protection** : Current Limit, Thermal Protection, Lock Protection
- ◆ **Insulation Class** : A (105°C)
- ◆ **Frame Material** : BMC
- ◆ **Lead wire exit** : Variable

◆ **Certification** : 

SPECIFICATION

Model	Voltage (V)	Output Watts [W]	Speed [r/min]	Efficiency (%)	FG Output (Pulse/Rev)	Shaft Diameter (mm)	Frame Material	Status
DLA4885 TYPE (PAM)	DC 12	~ 2.5 Max.	~ 3800	~ 50 Max.	4	Φ3,17	BMC	Present
DLB4885 TYPE (PWM)	DC 12	~ 2.5 Max.	~ 3800	~ 50 Max.	4	Φ3,17	BMC	Present

- **DIMENSIONS** ▷ DLA4885 TYPE (PAM) : 3-WIRE (VCC / FG / GND), Speed Control : Vcc Input Voltage Control
 ▷ DLB4885 TYPE (PWM) : 4-WIRE (VCC / VSP / FG / GND), Speed Control : PWM Control

Unit : mm

